

# WATERPROOF pH TESTERS

*... the next generation*

## Waterproof pHTestr® 10

±0.1 pH Accuracy; ATC

## Waterproof pHTestr® 20

±0.01 pH Accuracy; ATC

## Waterproof pHTestr® 30

±0.01 pH Accuracy; ATC;  
Temperature display



- Large Screen Display
- Up to ±0.01 pH Accuracy
- User Replaceable Double Junction, Polymer Sensor
- Up to 3-point (USA or NIST) Push Button Calibration with Auto-Buffer Recognition
- Simultaneous Temperature Display in °C or °F (Only in pHTestr 30)
- Automatic Temperature Compensation
- Extended Battery Life (More than 500 hours)

**EUTECH**  
**INSTRUMENTS**

*Technology Made Easy ...*

**Waterproof  
LARGE SCREEN  
pH Testers**



Large LCD Display

## LARGE DISPLAY SCREEN

Large dual-display LCD for enhanced readability. Important meter functions such as mode, ATC, battery level and temperature (pHTestr 30 only) are clearly displayed for your convenience, at all times.

## TEMPERATURE DISPLAY

pHTestr 30 displays both the pH and temperature values, simultaneously. pH is displayed on the top of the screen, while temperature is on the secondary display. You can choose to read temperature in °C or °F.

## CALIBRATION BUFFER SETS

Choose either the USA (pH 4.01, pH 7.00 and pH 10.01) or NIST (pH 4.01, pH 6.86 and pH 9.18) buffer sets.

## PUSH-BUTTON CALIBRATION WITH BUFFER RECOGNITION

Calibration is quick and easy with simple two-button operation. In the calibration mode, your pocket tester auto-detects and displays buffer value in the lower display, thus minimizing calibration errors. Three-point calibration ensures accuracy across the pH Scale. Reset calibration data to factory default setting whenever sensor is replaced.

## USER-REPLACEABLE DOUBLE-JUNCTION SENSOR

Replace the sensor yourself! No tools or messy soldering is necessary. Sensors are equipped with a double-junction construction minimizing reference element poisoning. Spare sensors are supplied separately.



User Replaceable Sensor



Twist-off Battery Compartment



Lanyard Connection



## NON-VOLATILE MEMORY

Your calibration data is safe when you power-off or change the batteries. EEPROM retains all the vital information.

## AUTO-POWER OFF

Meter automatically powers-off after 8.5 minutes of non-use to conserve battery life and save you money.

## HOLD FUNCTION

Hold measured values for later reading and recording, especially useful when you are in dimly lit and confined areas.

## SELF-DIAGNOSTIC MESSAGES:

- : Battery power-level indicator
- Or / Ur : Over or under-range, for pH and Temperature (pHTestr 30) values
- ATC / Or / Ur : When blinking, problem associated with the temperature sensor
- Er.0 : Temperature calibration error
- Er.1 : pH calibration error

## WARRANTY

Eutech Instruments warrants its testers free from manufacturing defects for 2 years and electrodes for 6 months.

## APPLICATIONS

- Water & wastewater treatment • Aquariums • Pool & spa water
- Hydroponics • Cooling towers • Aquaculture • Agriculture • Water quality testing • Boilers • Ecology studies • and more.

## METER SPECIFICATIONS

Model	pHTestr10	pHTestr20	pHTestr30
pH Range	-1.0 to 15.0 pH	-1.00 to 15.00 pH	
Resolution	0.1 pH	0.01 pH	
Accuracy	±0.1 pH	±0.01 pH	
Calibration Points	Up to 3 points		
Calibration Buffer Option	USA - pH 4.0 / 7.00 / 10.0 NIST - pH 4.0 / 6.9 / 9.2	USA - pH 4.01 / 7.00 / 10.01 NIST - pH 4.01 / 6.86 / 9.18	
Automatic Temperature Compensation (ATC)	Yes		
Temperature Display			0 - 50.0 °C or 32.0 - 122.0 °F
Resolution			0.1 °C / °F
Accuracy			±0.5 °C / 0.9 °F
Temperature Calibration Window			±5 °C / 9 °F from default value
Sensor	Double Junction, Ag/AgCl system with polymer gel		
Auto-Power Off	After 8.5 minutes from last key press		
User Reset	Yes		
Non Volatile Memory	Yes		
LCD Display	Custom dual line display		
Power Requirement	4 x 1.5V "A 76" Micro Alkaline Batteries		
Battery Life	More than 500 hours		
Operating Temperature	0 - 50 °C		
Dimensions/Weight	Tester : 16.5 cm x 3.8 cm; 90 g Boxed : 22 cm x 6 cm x 5 cm; 170 g		

## ORDERING INFORMATION

Order No.	Item
PHTEST10	Waterproof pHTestr 10
PHTEST20	Waterproof pHTestr 20
PHTEST30	Waterproof pHTestr 30
EC-PHWSEN03	Replacement Double Junction Sensor for pHTestr 10, 20, 30
EC-POUCH01	Carrying pouch for tester
33X367001	Lanyard, Eutech
60X017004	Alkaline Button Cell Batteries (2 pieces per pack)

Eutech also provides tester accessories and calibration standards. Refer to separate brochures for information.

Note: We reserve the right to make changes, improvements and modifications to products shown.

Distributed By:

**EUTECH**  
INSTRUMENTS  
Technology Made Easy ...

**ISO 9001**  
CERTIFIED

[www.eutechinst.com](http://www.eutechinst.com)  
[marketing@eutechinst.com](mailto:marketing@eutechinst.com)

Singapore ♦ USA ♦ Netherlands ♦ Malaysia ♦ China